RediPower

Industrial





Ready when you are

Ratchet wrenches



RP9425

Small & handy

FEATURES

- 1/4" square drive
- Progressive tease throttle
- One of the smallest ratchets, only 165mm (6.5") long
- Easy change reverse mechanism

BENEFITS

- Ideal for tight access applications
- Quick direction change
- Variable speed & torque output
- Pin retainer for quick socket change



RP9429

High torque & Compact in 3/8"

FEATURES

- 3/8" square drive
- Full torque in reverse
- Compact head design

BENEFITS

- Ideal for disassembly operations
- High torque in small package
- Ideal for tight and deep access applications
- Pin retainer for quick socket change



RP9430

High torque & compact in 1/2"

FEATURES

- 1/2" square drive
- Full torque in reverse
- Compact head design

BENEFITS

- Ideal for disassembly operations
- High torque in small package
- Accommodates larger socket range
- Pin retainer for quick socket change



RP9431Q



RP9432Q


Same features as RP9431Q


1/2" square drive with accommodates larger socket range

Highest torque & low noise

FEATURES







- Full torque in reverse
- Lightweight composite body

BENEFITS

- Ideal for larger fasteners
- Ideal for disassembly operations
- Operator comfort
- Ratchet head protection
- Pin retainer for quick socket change

See accessories on page 9

| MODEL | PART NUMBER | SQUARE DRIVE | FREE SPEED | TORQUE RANGE MIN. MAX. | | | AIR CONSUMPTION | | OVERALL LENGTH | | NET WEIGHT | | NOISE LEVEL | SOUND POWER | VIBRATION | AIR INLET | |
|---------|----------------|-----------------|---------------|------------------------|-------|-----|--------------------|------|-------------------|-----|---------------|------|----------------|----------------|-----------|--------------|------|
| | | in. | rpm | Nm | ft lb | Nm | ft lb | l/s | cfm | mm | in. | kg | lb | dB(A) | dB(A) | m/s² | NPTF |
| RP9425 | 615 190 9425 | 1/4 | 200 | 7 | 5 | 20 | 15 | 4.7 | 10 | 165 | 6.5 | 0.85 | 1.9 | 87 | 98 | 6.2 | 1/4" |
| RP9429 | 615 190 9429 | 3/8 | 150 | 14 | 10 | 68 | 50 | 7.5 | 16 | 254 | 10 | 1.20 | 2.6 | 97 | 108 | 7.9 | 1/4" |
| RP9430 | 615 190 9430 | 1/2 | 150 | 14 | 10 | 68 | 50 | 7.5 | 16 | 254 | 10 | 1.20 | 2.6 | 97 | 108 | 7.9 | 1/4" |
| RP9431Q | 615 190 9431 | 3/8 | 190 | 14 | 10 | 122 | 90 | 18.5 | 39 | 305 | 12 | 1.20 | 2.7 | 79 | - | 14.8 | 1/4" |
| RP9432Q | 615 190 9432 | 1/2 | 190 | 14 | 10 | 122 | 90 | 18.5 | 39 | 305 | 12 | 1.20 | 2.7 | 79 | - | 14.8 | 1/4" |