



Sanding & Polishing

PRO's range of sanding and polishing tools deliver surface finishing at its best. For rough surface sanding, choose pistol grip sanders and belt sanders. Random orbital sanders fit

the bill for coarse and fine sanding. For optimal surface polishing, angle grinders get the job done.



SANDERS

With unequalled power-to-weight ratio, the G2510-series is the most powerful angle sander in the PRO range. Choose between two different rotational speeds for surface grinding with various grits.

PRO G2510 With speed governor	S066	S085
Speed	6600 r/min	8500 r/min
Output	800 w	800 w
Recommended pad size	180 mm	180 mm
Spindle thread	M14	M14
Vibration level	<2.5 m/s ²	2.6 m/s ²
Sound level	75 dB(A)	78 dB(A)
Length	207 mm	207 mm
Weight	1.4 kg	1.4 kg
Air consumption	17 l/s	17 l/s
Air inlet thread	3/8" BSP	3/8" BSP
Suitable air hose	13 mm (1/2")	13 mm (1/2")
Ordering No.	8423 0316 39	8423 0316 35





SANDERS

Enjoy a complete line of pistol grip sanders that handle virtually every need. Choose from the G2302 mini-pistol sander up to the powerful G2502 sander with pad sizes ranging from 50 mm (2") to 125 mm (5"). G2302 pads work with the 3M Roloc system. All PRO sanders feature adjustable speed controlled by the trigger and air exhaust through the handle.



PRO G2302

Speed	17 000 r/min
Pad size	3" 3M Roloc
Thread	1/4"-20 UNC
Output	175 w
Length	109 mm
Vibration level	< 2.5 m/s ²
Sound level	81 dB(A)
Weight	0.6 kg
Air consumption	8.9 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 14



PRO G2302 Kit

Complete set with 2" and 3" backup pads. 10 of each sanding discs 60-80-120 grit for 2" and 3", 3 of each 2" and 3" surface preparation pads (fine, medium and coarse).

Speed	17 000 r/min
Pad size	3" 3M Roloc
Output	175 w
Length	109 mm
Vibration level	< 2.5 m/s ²
Sound level	81 dB(A)
Weight	0.6 kg
Air consumption	8.9 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 15



PRO G2402

Speed	12 000 r/min
Pad size	125 mm (5")
Thread	7/16" UNF
Output	200 w
Length	124 mm
Vibration level	< 2.5 m/s ²
Sound level	82 dB(A)
Weight	1 kg
Air consumption	12 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 02



PRO G2502

Speed	12 000 r/min
Pad size	125 mm (5")
Thread	7/16" UNF
Output	270 w
Length	108 mm
Vibration level	< 2.5 m/s ²
Sound level	82 dB(A)
Weight	1 kg
Air consumption	12 l/s
Air inlet thread	1/4" BSPT
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 05



SANDERS

- Adjustable angle of arm • Air exhaust through handle.



PRO G2403

Rotational speed	18 000 r/min
Belt speed	1 300 m/min
Belt dimension	10 x 330 mm
Output	250 w
Length	280 mm
Vibration level	< 2.5 m/s ²
Sound level	85 dB(A)
Weight	0.8 kg
Air consumption	11 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0304 33



PRO G2404

Rotational speed	16 500 r/min
Belt speed	2 540 m/min
Belt dimension	20 x 520 mm
Output	400 w
Length	360 mm
Vibration level	< 2.5 m/s ²
Sound level	85 dB(A)
Weight	1.4 kg
Air consumption	11 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0304 44

Accessories belt sanders

Abrasives	G2403	G2404
50 grit	4170 1199 00	4170 1201 00
80 grit	4170 1196 00	4170 1197 00
120 grit	4170 1200 00	4170 1202 00

Accessories belt sanders

	Ordering No.
125 mm pad with nut (G2402)	4210 3766 00
Spanner for nut (G2402)	4210 3767 00

POLISHING SANDERS



PRO G2406

Speed	2 000 r/min
Output	350 w
Support pad	125 – 200 mm
Spindle thread	3/8"-24UNF
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Length	300 mm
Weight	1.4 kg
Air consumption	10 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0304 88



PRO G2407 / M14

Speed	3 400 r/min
Output	350 w
Support pad	125 – 200 mm
Spindle thread	3/8"-24UNF
Vibration level	< 2.5 m/s ²
Sound level	78 dB(A)
Length	300 mm
Weight	1.4 kg
Air consumption	10 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0304 77
	8423 0304 55 (M14)

RANDOM ORBITAL SANDERS



PRO G2301

Speed	17 000 r/min
Dia orbit	4 mm
Pad size	3" 3M
Output	175 w
Length	117 mm
Vibration level	5.6 m/s ²
Sound level	81 dB(A)
Weight	0.6 kg
Air consumption	8.9 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 10



PRO G2301-KIT

Complete set with 1 pcs each of 2" and 3" velcro sanding pad and 10 pcs each of 320-400-600 grit sanding paper for 2" and 3".	
Speed	17 000 r/min
Dia orbit	4 mm
Pad size	3" 3M
Output	175 w
Length	117 mm
Vibration level	5.6 m/s ²
Sound level	81 dB(A)
Weight	0.6 kg
Air consumption	8.9 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0312 11



PRO G2401

Speed	10 000 r/min
Dia orbit	5 mm
Pad size	150 mm
Thread	5/16"-24 UNF
Length	180 mm
Vibration level	< 2.5 m/s ²
Sound level	86 dB(A)
Weight	2 kg
Air consumption	7.7 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 0324 43

Accessories for G2401

Type	Ordering No.
Spot suction kit	3780 4017 30
Hose set for spot suction kit	3780 2724 40
Support pad	4112 0680 00



RANDOM ORBITAL SANDERS

For perfect coarse and fine sanding result, choose a lubrication-free PRO random orbital sander with 2.5, 5 or 10 mm orbit.



PRO G2438-N	G2438-6.3N	G2438-6.5N	G2438-6.10N
Without suction			
Speed	12 000 r/min	12 000 r/min	12 000 r/min
Output	160 w	160 w	160 w
Dia orbit	2.5 mm	5 mm	10 mm
Pad size	150 mm	150 mm	150 mm
Velcro pad	No hole version	No hole version	No hole version
Spindle thread	5/16" UNF	5/16" UNF	5/16" UNF
Vibration level	< 2.5 m/s ²	< 2.5 m/s ²	< 2.5 m/s ²
Sound level	79 dB(A)	79 dB(A)	79 dB(A)
Length	170 mm	170 mm	170 mm
Weight	0.9 kg	0.9 kg	0.9 kg
Air consumption	9 l/s	9 l/s	9 l/s
Air inlet thread	1/4" BSP	1/4" BSP	1/4" BSP
Suitable air hose	10 mm (3/8")	10 mm (3/8")	10 mm (3/8")
Ordering No.	8423 0313 10	8423 0313 05	8423 0313 12



PRO G2428 **Two hand model**

Speed	9 025 r/min
Dia orbit	10 mm
Pad size	150 mm
Velcro pad	6 hole version
Spindle thread	5/16" UNF
Vibration level	< 2.5 m/s ²
Sound level	92 dB(A)
Length	170 mm
Weight	1.5 kg
Air consumption	9 l/s
Air inlet thread	1/4" BSP
Suitable air hose	10 mm (3/8")
Ordering No.	8423 2810 16



PRO G2438-I	G2438-6.3I	G2438-6.5I	G2438-6.10I
Internal self suction, dust bag included			
Speed	12 000 r/min	12 000 r/min	12 000 r/min
Output	160 w	160 w	160 w
Dia orbit	2.5 mm	5 mm	10 mm
Pad size	150 mm	150 mm	150 mm
Velcro pad	6 hole version	6 hole version	6 hole version
Spindle thread	5/16" UNF	5/16" UNF	5/16" UNF
Vibration level	< 2.5 m/s ²	< 2.5 m/s ²	< 2.5 m/s ²
Sound level	79 dB(A)	79 dB(A)	79 dB(A)
Length	235 mm	235 mm	235 mm
Weight	1.0 kg	1.0 kg	1.0 kg
Air consumption	9 l/s	9 l/s	9 l/s
Air inlet thread	1/4" BSP	1/4" BSP	1/4" BSP
Suitable air hose	10 mm (3/8")	10 mm (3/8")	10 mm (3/8")
Ordering No.	8423 0313 20	8423 0313 15	8423 0313 17

Accessories, pads

150 mm for G2428

150 mm Velcro 6 hole	4112 6103 16
150 mm Vinyl 6 hole	4112 6105 06
150 mm Velcro no hole	4112 6102 10
150 mm Vinyl no hole	4112 6104 00

Accessories, pads

125 mm for G2438

<2.5 m/s² vibration




	Ordering No.
125 mm Velcro 5 hole	4112 6106 04
125 mm Vinyl 5 hole	4112 6106 02
125 mm Vinyl no hole	4112 6106 01
125 mm Velcro no hole	4112 6106 03



PRO G2438-C	G2438-6.3C	G2438-6.5C	G2438-6.10C
Central suction			
Speed	12 000 r/min	12 000 r/min	12 000 r/min
Output	160 w	160 w	160 w
Dia orbit	2.5 mm	5 mm	10 mm
Pad size	150 mm	150 mm	150 mm
Velcro pad	6 hole version	6 hole version	6 hole version
Spindle thread	5/16" UNF	5/16" UNF	5/16" UNF
Vibration level	< 2.5 m/s ²	< 2.5 m/s ²	< 2.5 m/s ²
Sound level	79 dB(A)	79 dB(A)	79 dB(A)
Length	215 mm	215 mm	215 mm
Weight	0.9 kg	0.9 kg	0.9 kg
Air consumption	9 l/s	9 l/s	9 l/s
Air inlet thread	1/4" BSP	1/4" BSP	1/4" BSP
Suitable air hose	10 mm (3/8")	10 mm (3/8")	10 mm (3/8")
Ordering No.	8423 0313 30	8423 0313 25	8423 0313 27



ACCESSORIES FOR G2406

	Accessories	Ordering No.
	150 mm Velcro pad, thread UNC 5/8". Maximum speed 2 500 r/min. To be used together with velcrosponge heads or Velcro lamb'swool bonnet.	4112 6092 15
	Lamb's-wool bonnet 150 mm with Velcro fitting. Maximum speed 2 500 r/min.	4112 6093 15
	150 Velcro sponge head, maximum speed 2 500 r/min, White , Dense, firm sponge head for compounding 2-pack paint systems. Excellent result with all leading makes of compound and polish.	4112 6094 15
	200 mm Velcro sponge head, maximum speed 2 500 r/min, White , Dense, firm sponge head for compounding 2-pack paint systems. Excellent result with all leading makes of compound and polish.	4112 6095 20
	150 mm Velcro sponge head, maximum speed 2 500 r/min, Blue Softer sponge, more open cell, for polishing and compounding of cellulose, acrylics etc.	4112 6096 15
	200 mm Velcro sponge head, maximum speed 2 500 r/min, Blue Softer sponge, more open cell, for polishing and compounding of cellulose, acrylics etc.	4112 6097 20
	150 mm Velcro sponge head, maximum speed 2 500 r/min, Pink Ultra soft, particularly good for dark colours.	4112 6098 15
	150 mm Velcro sponge head, maximum speed 2 500 r/min, Yellow coarse sponge, open cell, for aggressive compounding including oxidised paintwork.	4112 6099 15

ACCESSORIES FOR G2406 AND G2407

			
150 mm white sponge head pad, thread UNC 5/8". Maximum speed 4 000 r/min.	150 mm blue sponge head pad, thread UNC 5/8". Maximum speed 4 000 r/min.	180 mm soft plastic UNC 5/8" and spanner. Maximum speed 8 000 r/min.	UNF 3/8"-24 x M14 Spindle thread adaptor. (To be used with M14 threaded ads.)
Ordering No. 4112 6100 15	Ordering No. 4112 6101 15	Ordering No. 4170 0756 80	Ordering No. 4021 0435 00
			Exhaust air hose Ordering No. 4150 1077 80