



Screwdrivers

For unmatched precision fastening, use PRO screwdrivers. These highly engineered fastening tools meet the demands for industrial performance, accuracy and durability.

Four different clutch types are available: impact drive, direct drive, slip clutch and shut-off coupling. Well-balanced for ergonomics, PRO screwdrivers take productivity to a whole new level.



SCREWDRIVERS

For fast assembly and disassembly, PRO Impact Drive Screwdrivers with double hammer get the job done. Designed for the ultimate in operator

comfort, these lightweight tools deliver exceptional performance. Both models are reversible with a simple flip off lever on the side of the tool shaft.

PRO S2480 IMPACT DRIVE

Chuck size	1/4" Hex QC
Clutch type	Double hammer
Capacity	M5
Torque range	6-13 Nm
Max torque	20 Nm
Speed	6 500 r/min
Weight	0.78 kg
Length	132 mm
Vibration level	0.32 m/s ²
Sound level	77 dB(A)
Air consumption	10 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4 BSP
Ordering No.	8431 0257 90



PRO S2481 IMPACT DRIVE

Chuck size	1/4" Hex QC
Clutch type	Double hammer
Capacity	M6
Torque range	11-20 Nm
Max torque	28 Nm
Speed	5 000 r/min
Weight	0.88 kg
Length	143 mm
Vibration level	0.28 m/s ²
Sound level	79 dB(A)
Air consumption	8 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4 BSP
Ordering No.	8431 0257 92



PRO Direct Drive Screwdrivers stall when they reach max torque and are well suited for self-

drilling screws and wood screws.

PRO S2305 DIRECT DRIVE

Chuck size	1/4" Hex QC
Capacity	M8
Wood screw	No 12
Torque range	-12 Nm
Speed	750 r/min
Weight	0.9 kg
Length	198 mm
Vibration level	< 2.5 m/s ²
Sound level	76 dB(A)
Air consumption	5.6 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 28



PRO S2326 DIRECT DRIVE

Chuck size	1/4" Hex QC
Capacity	M6
Wood screw	No 8
Torque range	-4.5 Nm
Speed	2 400 r/min
Weight	0.8 kg
Length	178 mm
Vibration level	< 2.5 m/s ²
Sound level	76 dB(A)
Air consumption	5.6 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 36





SCREWDRIVERS

PRO Slip-Clutch Screwdrivers provide an implied pulsating force, or “slips”, once you reach the desired torque. Top features include adjustable torque settings, wings for comfort, trigger and push start for pistol grips, and

lever and push start for straight models. These screwdrivers are suitable for soft joints or when the torque level may temporarily peak during the homing phase when using sheet metal screws, wood screws or self-tapping screws.

PRO S2308-C SLIP CLUTCH

Chuck size	1/4" Hex QC
Capacity	M6
Torque range	2.5-11 Nm
Speed	950 r/min
Weight	1.1 kg
Length	225 mm
Vibration level	3.7 m/s ²
Sound level	77 dB(A)
Air consumption	8.4 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 20



PRO S2340-C SLIP CLUTCH

Chuck size	1/4" Hex QC
Capacity	M3
Torque range	0.5-2 Nm
Speed	1 300 r/min
Weight	0.9 kg
Length	250 mm
Vibration level	< 2.5 m/s ²
Sound level	72 dB(A)
Air consumption	4.0 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 40



PRO S2370-C SLIP CLUTCH

Chuck size	1/4" Hex QC
Capacity	M5
Torque range	2-6 Nm
Speed	1 300 r/min
Weight	0.9 kg
Length	250 mm
Vibration level	< 2.5 m/s ²
Sound level	72 dB(A)
Air consumption	4.0 l/s
Suitable air hose	6.3 mm (1/4")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 70



PRO Shut-off Screwdrivers have fast and accurate shut-off clutch for smooth performance and

high quality tightening. They are ideal for joints which require high accuracy in torque.


PRO S2450-P SHUT-OFF

Chuck size	1/4" Hex QC
Capacity	M5
Torque range	2.4-5 Nm
Speed	1 100 r/min
Weight	1.1 kg
Length	225 mm
Vibration level	< 2.5 m/s ²
Sound level	75 dB(A)
Air consumption	6.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 84



PRO S2416-L SHUT-OFF

Chuck size	1/4" Hex QC
Capacity	M3
Torque range	0.5-1.6 Nm
Speed	1 500 r/min
Weight	0.9 kg
Length	230 mm
Vibration level	< 2.5 m/s ²
Sound level	71 dB(A)
Air consumption	6.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 82



PRO S2426-L SHUT-OFF

Chuck size	1/4" Hex QC
Capacity	M4
Torque range	1.2-2.6 Nm
Speed	1 500 r/min
Weight	0.9 kg
Length	230 mm
Vibration level	< 2.5 m/s ²
Sound level	71 dB(A)
Air consumption	6.0 l/s
Suitable air hose	10 mm (3/8")
Air inlet thread	1/4" BSP
Ordering No.	8431 0257 80















ACCESSORIES - SCREWDRIVERS

Type	Ordering No.
Holder for insert bits Magnetic holder 	4023 0707 00

UNIVERSAL JOINTS

	Size	Ordering No.
Slotted 	Blade width mm	Extra hard
	3.4	4023 1400 21
	3.9	4023 1400 22
	4.7	4023 1400 23
	5.5	4023 1400 26
	6.3	4023 1400 27
	7.0	4023 1400 28
Phillips 	Point size	Extra hard
	1	4023 0696 01
	2	4023 0697 01
Pozi driv 	Point size	Extra hard
	1	4023 1101 11
	2	4023 1101 12
Torx 	Point size	Medium hard
	T10	4023 1321 00
	T15	4023 1331 00
	T20	4023 1322 00
Allen head 	mm/in	Extra hard
	3	4023 0819 00
	4	4023 1320 00
	5/32	4023 0705 00
	5	4023 0820 00
6	4023 0821 00	

POWER BITS 1/4"

	Size	Ordering No.
Slotted 	Blade width mm	Extra hard
	4.7	4023 2020 24
	6.3	4023 2020 26
	7.0	4023 2020 27
	7.9	4023 2020 28
	9.1	4023 2020 29
Phillips 	Point size	Extra hard
	1	4023 2320 21
	2	4023 2320 22
Pozi driv 	Point size	Extra hard
	1	4023 2420 21
	2	4023 2420 22
Torx 	Point size	Medium hard
	T10	4023 2220 23
	T15	4023 2220 24
	T20	4023 2220 25
Allen head 	mm/in	Extra hard
	3	4023 0710 00
	4	4023 0711 00
	5/32	4023 0681 00
	5	4023 0712 00
6	4023 0906 00	

